



BOA SP10

Annularly corrugated metal hose assembly DIN-DVGW certified and VdS approved

The annularly corrugated metal hose assembly **SP10** has a medium corrugation and a stainless steel braid. One side inert gas welded, malleable cast iron nipple with male thread according to ISO 7-1, the other side inert gas welded three-part, conical sealing malleable cast iron screw connection with female thread according to ISO 7-1, DIN-DVGW-certificate, VdS approved.

Working conditions

 $\begin{array}{lll} \mbox{Min. admissible temperature:} & 9 \mbox{ max, adm.} & = -20 \mbox{°C} \\ \mbox{Max. admissible temperature:} & 9 \mbox{ max, adm.} & = +300 \mbox{°C} \\ \end{array}$

Nominal pressure rate general: PN25

- for fluids, gases & steams: $\begin{array}{ll} p_{\text{ max, working.}} = 25 \text{ bar until } \vartheta_{\text{ working}} \leq 120^{\circ}\text{C} \\ p_{\text{ max, working.}} = 20 \text{ bar at } 120^{\circ}\text{C} < \vartheta_{\text{ working}} \leq 300^{\circ}\text{C} \end{array}$

- for combustion gases (acc. to DIN 3384): p $_{\text{max, working}}$ = PN5 bar at ϑ $_{\text{working}}$ = 20°C

Application fields:

- gas applications
- heating, ventilation, air conditioning
- mechanical engineering
- hydraulic engineering

Materials:

Corrugated hose stainless steel 1.4404 stainless steel 1.4301 malleable cast iron (weldable)

DN	Thread	Nominal pressure PN	Nominal length NL	Weight	BOA item n°
[mm]	["]	[bar]	[mm]	[kg]	[-]
10	R ³ / ₈ "A" Rp ³ / ₈ "	25	300	0.20	6000076423
			500	0.26	6000076424
			1000	0.41	6000076425
12 (16)	R ½" A Rp ½"	25	300	0.25	6000076414
			500	0.31	6000076415
			1000	0.47	6000076416
20	R ¾" A Rp ¾"	25	500	0.55	6000076426
			750	0.67	6000076427
			1000	0.79	6000076428
25	R 1"A Rp 1"	25	500	0.80	6000076417
			750	0.95	6000076429
			1000	1.10	6000076418
32	R 1¼" A Rp 1¼"	25	500	1.30	6000076430
			750	1.52	6000076431
			1000	1.75	6000076432
40	R 1½" A Rp 1½"	25	500	1.45	6000076419
			750	1.75	6000076433
			1000	2.03	6000076420
50	R 2" A R 2"	25	500	2.40	6000076421
			750	2.90	6000076434
			1000	3.35	6000076422

Preferred series; usually available at short term

Useful data for placing an inquiry or order:

Item description: BOA SP10
BOA item n° (M-)

DN

Quantity

The three leaflets for metal hoses and metal hose assemblies "Technical Information", "Installation Instructions" and "Guarantee/ Delivery terms/ Conditions" are integrating part of the present product data sheet.

Specifications subject to change without notice.